

Declaration of Performance
According annex III of the regulation (EU) No. 305/2011

for the production of [sheets, coils and plates made of aluminium]

Nr. [EN AW 5754 H111]

1. Unique identification code of the product- type:
sheets, coils and plates made of aluminium
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
sheets, coils and plates made of aluminium
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer.
sheets, coils and plates for structural applications made of aluminium
according to EN 15088 : 2006-03
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
AMAG rolling GmbH
P.O. Box 32
A-5282 Ranshofen
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
system 2+
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The notified body [TÜV SÜD Industrie Service GmbH], identification number [No. 0036], has performed the initial inspection of the factory and the factory production control as well as the continuing control and evaluation of the factory production control under system 2+ and issued:
Certificate of conformity of the factory production control
[0036-CPD – M 46 – 2011]
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not relevant



9. Declared performance

Essential characteristics [see Note 1]		Performance [see Note 2]				Harmonised technical specification (see Note 3)	
Mechanical properties							
Nominal Thickness from - to [mm]	Tensile strength Rm [MPa]		Yield strength Rp0,2 [Mpa]		Elongation [%]		EN 485-2
	min.	max.	min.	max.	A50	A	
0,2 - 0,5	190	240	80		12		
0,5 - 1,5	190	240	80		14		
1,5 - 3,0	190	240	80		16		
3,0 - 6,0	190	240	80		18		
6,0 - 12,5	190	240	80		18		
12,5 - 100,0	190	240	80			17	
Chemical composition							
according to						EN 573-3	
Dimensions and form tolerances							
length, width, thickness						EN 485-3, EN 485-4	
Bendability							
Bendability class		B1				EN 15088	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

[Anton Eberle, Managing Director AMAG rolling]
(name and function)

[Ranshofen am 05.06.2013]
(place and date of issue)


.....
(signature)

